


|                  |                                          |
|------------------|------------------------------------------|
| Function         | Broken probe extraction 100mil           |
| Probe attributes | Test probes with barrel OD appr. Ø1,35mm |
| Handle           | H-2.6                                    |
| Replacement BIT  | BIT-BPET-135                             |
| Locking          | DIN 913 M3x3 screw                       |
| Tool length      | 92mm                                     |
| Maximum reach    | ~20mm                                    |



## Compatibility

| Probe Manufacturer | Compatible series<br>(examples)                                                                                                                                       |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ECT                | BTP-25 / BPLT-25 / EPA-2 / FRP-25T / GSP-2B<br>HCP-25 / HPA-64 / HPA-74 / LFLT-25 / LFRE-25<br>LTP-25 / MSP-25C / P2664 / POGO-25<br>RSP-2T / SPA-2 / SPA-64 / STP-25 |
| Feinmetall         | F100 / F320 / F502 / F504 / F538 / F562 / F558<br>F585 / F670 / F704 / F708 / F731 / F751 / F771<br>F865 / F864                                                       |
| Fixtest            | 21 / 29 / 70 / 100 / 101 / 120 / 125 / 211 / V100X                                                                                                                    |
| Ingun              | DKS-100 / E-100 / GKS-002 / GKS-100<br>GKS-135 / GKS-899 / GKS-938 / GKS-945<br>GKS-946 / GKS-961 / HMS-100 / SKS-100<br>T-899                                        |
| PTR                | 1015 / 1015.50 / 1015/G / 1016 / 1018 / 1018.06<br>1025/E / 1025/D / 1034/E / 1036/E / 3030                                                                           |
| QA Tech            | 100-05 / 100-16 / 100-25 / 100-40 / 100-50<br>100-12 / 100-15 / 100-24 (interface probes)                                                                             |